



Partners in Progress Since 1948

# Model 616 Vertical Electric Prop Agitator

## High-Performance Prop Agitator for a Consistent Blend!



Agitate **FAST!** Blend **FAST!**

- Pivots easily, fast agitating, quick consistent blending of dairy or hog manure.
- Energy Efficient – low horsepower requirements! Use 7-1/2, 10 or 15 HP electric motor.
- Unique seal system extends gearbox and bearing life!
- Abrasion-resisting steel propeller blades & shear plate with stainless steel hardware below the liquid line for long life!
- Agitator available in various lengths 6 to 16 feet (1.8 to 4.8 m).
- Easy lube – convenient 'above pit' oil and grease lines.
- Easy view oil level monitoring.
- Easy to install anchored pivot allows precise positioning to agitate entire pit.




*(Please see reverse side for details.)*



# More Features and Benefits

**Model 616 - an affordable & efficient way to move your manure.**

This agitator handles fibrous waste for versatile uses! The propeller blades' design increases agitation efficiency for high-volume flow for maximum agitation.



Protection against bearing contamination. The lower gearbox output shaft has four seals to keep contaminants out.

Adjustable shear plate located close to the propeller chops and homogenizes material for a more uniform consistent blend.

Propeller blades are heavy, abrasion resisting steel for long life.

Lifting holes located on top of the pump allows easy insertion and removal of the unit in the pit with a tractor loader, skid-steer loader or winch.

An anchored pivot is included as standard equipment to allow you to precisely position the agitator to agitate the entire pit. Plate must be lagged to a concrete pad or curb.



Foot locking pedal allows rotation of the agitator to handle many types of slurry waste and improve pit cleanout.

Choice of agitation volumes. Patz offers a choice of electric motors (7½, 10 or 15 HP) and pulleys to match your agitation requirements.



Unique seal system extends gearbox bearing life. Gearbox bearing seals can be purged every 8 hours.

Easy access to oil reservoir. End guessing - inspect oil level conveniently. A large fill hole allows easy access for adding oil to the gearbox. (Patz recommends using a non-detergent oil.)



**CAUTION:** Never operate Patz equipment without all shields and guards in place. Safety is no accident. Before operating any piece of equipment, be sure to read and understand the operators manual. The manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place.



*For some photos in this brochure, guards were removed for photographic purposes only to allow viewing of the equipment features. Before operating equipment, all guards must be in place. Because Patz continually improves and updates products, Patz reserves the right to change the construction of machines or attachments or any part thereof without incurring any obligation to make like changes on Patz machines, or attachments previously delivered.*

*Specifications and prices subject to change without notice.*



Patz Corporation  
917 Business 141, P.O. Box 7  
Pound, Wisconsin 54161-0007  
Phone: 920-897-2251  
Fax: 920-897-2142  
www.patzcorp.com  
info@patzcorp.com

**PARK LAKE EQUIPMENT SALES**  
**Toll-Free 1-800-567-4706**  
**Lethbridge, AB. 403-381-4706**  
**Lethbridge, AB. c 403-382-0457**  
**Red Deer, AB. c 403-634-4477**

[www.parklakeequipmentsales.ca](http://www.parklakeequipmentsales.ca)